

Encube Series VC12200 Plus

12V LiFePO₄ Li-ion Battery



Cell Balancing, Extend lifetime of battery. Current >300mA



Safe and reliable
The safest LFP battery cell



Bluetooth built-in
Easy to access battery status



Battery management system with chip



Supports series and parallel use



High compatibility
Support to connect with lead-acid battery

Application Scenario




RV



Solar light



Golfcart



Marine



Camera



Household



Website: www.power-revolution.co.za



E-mail: brendon@power-revolution.co.za



TEL +27 82 572 4756

Electrical

Nominal Voltage/V	12.8
Nominal Capacity/Ah	200
Rated Energy/Wh	2560
BMS Function	Overcharge, overdischarge, overcurrent and temperature protection
Recommended Charge Voltage/V	14.4 - 14.6
Discharge Cut-off Voltage/V	10.8
Standard Charge Current/A	50
Max. Charge Current/A	100
Continuous Discharge Current/A	100
Peak Discharge Current/A@5S	400
Voltage Configurations	12,24,36 or 48V
Maximum Configuration	Increase capacity in series or increasing voltage parallel
Maximum Time Between Charges	3 months
Monitoring	Bluetooth

Mechanical

Dimension(L*W*H)/ mm	520*270*220
Weight/kg	Approx.31.5
Terminal	M8
Casing material	ABS

Environment

Working Temperature Range/°C	Charge : 0~55 Discharge: -20~60
Humidity Range/RH	< 95%
Storage temperature/°C	15~35
IP protection level	IP65

